



Z-Select 2000D 190 Tag

Paper Tag

Direct Thermal

A premium topcoated direct thermal 185 micron white tag stock which produces high contrast black images with Zebra thermal printers. This product has very good resistance to image fading under UV light. It is not recommended for applications involving extended exposure to moisture and exposure to solvents.

Note: Z-Select 2000D 190 Tag is not recommended for applications involving long term exposure to direct sunlight or extreme heat.

Suggested Applications

- Packaging inserts
- Pallet tags
- Inventory control and shop floor tracking tickets
- Admission tickets
- Visitor name tags
- Passenger tickets in public transport applications
- Shelf-edge tags

Technical Specifications

	Description	Caliper
Facestock	185 gsm. white thermal imaging paper tag	185 microns \pm 11%

Recommended Zebra Printers: Mid-range and high-performance thermal printers

Recommended Zebra ribbons: N/A

Minimum Application Temperature: N/A

Service Temperature Range: -5°C to 49°C

Recommended Storage Conditions: Six months duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order sample roll SAM5222.